


# Mech-Eye Industrial 3D Camera

NANO ULTRA-GL

Technical Specifications V3.0



## Physical Specifications

Model	NANO ULTRA-GL
Dimensions <sup>[1]</sup>	125 × 46 × 76 mm
Weight <sup>[1]</sup>	0.7 kg
Baseline	86 mm
Light source	Blue LED (440 nm, RG2)
2D image color	Monochrome
Operating temperature	0–45°C
Operating humidity	0–85%RH, non-condensing
Storage temperature	-20–60°C
Communication interface	Gigabit Ethernet
Input	24 VDC, 3.75 A
Power	Idle: 8 W Average: 12 W Peak: 37 W
IP rating <sup>[2]</sup>	IP65
Cooling	Passive
Flatness tolerance for mounting surface <sup>[3]</sup>	± 0.05 mm
Vibration resistance <sup>[4]</sup>	Sinusoidal vibration along the X-, Y-, and Z-axes, 10–57 Hz, 1.5 mm peak-to-peak value, 3 hours per axis
Shock resistance <sup>[5]</sup>	Half sine shock pulses along the positive and negative directions of the X-, Y-, and Z-axes, 147 m/s <sup>2</sup> (15 g), 11 ms, 3 shocks per direction, 18 shocks in total

[1] Heat-dissipation panel not included.

[2] Test implemented based on IEC 60529. 6: dust-tight; 5: waterproof.

[3] The flatness of the surface used to mount the camera should satisfy this requirement.

[4] Test implemented based on IEC 60068-2-6.

[5] Test implemented based on IEC 60068-2-27.

# Performance Specifications

Working distance	250-500 mm	400-800 mm
Recommended working distance	250-500 mm	400-800 mm
Object focal distance <sup>[1]</sup>	350 mm	700 mm
FOV (near)	220 × 165 mm @ 0.25 m	400 × 270 mm @ 0.4 m
FOV (far)	500 × 340 mm @ 0.5 m	770 × 550 mm @ 0.8 m
Resolution <sup>[2]</sup>	2400 × 1800	
Typical capture time <sup>[3],[4]</sup>	0.5-0.9 s	
Recommended warm-up time <sup>[3],[5]</sup>	30 min	
Point Z-value repeatability (1σ) <sup>[3],[6]</sup>	0.045 mm @ 0.4 m	0.1 mm @ 0.6 m
Measurement accuracy (VDI/VDE) <sup>[3],[7]</sup>	0.1 mm @ 0.4 m	0.1 mm @ 0.6 m

[1] The object focal distance of the 2D camera inside the product.

[2] Can be changed to 1200 × 900 through Mech-Eye Viewer.

[3] Unless otherwise specified, this test was conducted under the standard test conditions listed on page 8.

[4] The range of time taken to acquire depth data in the "Fast" and "Accurate" fringe coding mode.


[5] The recommended warm-up time required to guarantee data accuracy to the listed values. For the warm-up method, refer to the user manual (The data acquisition interval is 10 s). Please adjust the warm-up time based on the actual data acquisition interval, ambient temperature, and heat-dissipation conditions.

[6] The standard deviation of the 100 measured depth values of each point on the target object was calculated, and then the median of all the standard deviations was taken. The target object was a white 95% alumina ceramic plate with a rough surface. The Point Cloud Processing parameters were set to "Off".


[7] Test implemented with reference to VDI/VDE 2634 Part 2.

# FOV

## Object Focal Distance: 350 mm




## Object Focal Distance: 700 mm




# Spatial Resolution

Object Focal Distance: 350 mm




Object Focal Distance: 700 mm




# Point Z-Value Repeatability

Object Focal Distance: 350 mm




Object Focal Distance: 700 mm



# Dimensions

Unit: mm



\* Without the camera bracket and heat-dissipation panel

## Certifications



Hereby [Mech-Mind Robotics Technologies Ltd.] declares that [NANO ULTRA-GL] is in compliance with the Electromagnetic Compatibility Directive 2014/30/EU.

The full text of the EU Declaration of Conformity is available at:  
<https://downloads.mech-mind.com/?tab=tab-eu-dec>



R-R-viz-MM010



## Standard Testing Conditions

Working distance <sup>[1]</sup>		250-500 mm 400-800 mm	
Ambient temperature		15-30°C	
Ambient humidity		0-85%RH, non-condensing	
Ambient light		200-1000 lx	
Camera parameters <sup>[2]</sup>	Exposure Time: 3D		10 ms
	Exposure Mode: 2D		Timed (Exposure Time: 80 ms)
	Gain		0 dB
	Light Brightness		High
	Fringe Coding Mode		Accurate
	Point Cloud Processing	Outlier Removal	Normal
		Noise Removal	Normal
Surface Smoothing		Normal	
Tested region <sup>[3]</sup>		Length: 90% of FOV length Width: 90% of FOV width Position: center of FOV	
Resolution		2400 × 1800	

[1] For the object focal distance of 350 mm, the working distance used in tests is 250-500 mm. For the object focal distance of 700 mm, the working distance used in tests is 400-800 mm.

[2] Parameters not listed are set to their default values.

[3] Test data was obtained from this region.