

# Wirefeed Unit CM-0401-D

The CM-0401-D wire feed unit is a component that has been specially developed for ARXIS welding power sources.

The CM-0401-D wire feed unit is a component that has been specially developed for ARXIS welding power sources. It enables precise and controlled feeding of the welding wire during the welding process. This unit ensures a reliable wire feed speed and thus contributes to uniform and high-quality weld seam formation.



## Specification

Type	CM-0401-D
Anwendbarer Drahtdurchmesser	Ø 0.6, - 2.4 mm
Werkseitige Einstellung des Kabelquerschnitts	Ø1.2 mm
Drahtvorschubgeschwindigkeit	1.5 – 22 m/min
Stromversorgung	DC 42 V
Motorstrom	2.5 A
Brenneranschluss	EURO
Gewicht des zu verwendenden Drahtes	Max. 25 kg
Schutzgas (maximaler Druck)	CO <sub>2</sub> , Ar, ArCO <sub>2</sub> mixture (0.4 MPa)
Art der Kühlung (maximaler Druck)	water, water/glycol mixture (0.5 MPa)
Maximal zulässige Belastung	500 A(60%) /430 A (100%)
Gehäuseklasse	IP23
Konformität Standard	IEC 60974-5
Temperaturbereich	10 ~ 40 °C
Feuchtigkeitsbereich	20 ~ 80% (no condensation)
Temperaturbereich bei Lagerung	-10 ~ 60 °C
Bereich der Lagerfeuchtigkeit	20 ~ 80% (no condensation)
Äußere Abmessungen (BxTxH)	317 mm x 775 mm x 392 mm
Gewicht	16 kg

## Product information

Order No. 254000018

Model No. 0