

MVL-MF1628M-8MP

2/3" 16mm 8MP FA LENS


MF series FA Lens are optimized for machine vision light sources and sensor, with high resolution, excellent image quality, high transmittance and good stability. Featured with fixed focal length, manual aperture and compact size, it is suitable for machine vision industry applications and ideal for industrial cameras.




Key Features

- Ultra-high resolution and consistency of image clarity
- Ultra-low distortion and higher relative illumination
- Achromatic optical system design, better image performance with color camera
- Supports ultra-short working distance with good optical performance
- Compact design, excellent vibration resistance and high and low temperature performance


Distortion



MTF



Relative Illumination




Note: The above curves are the simulate results based on F2.8, $\beta=-0.051$, WD=300 mm.



Specification

Model	MVL-MF1628M-8MP
Parameter	Fixed focal length, Manual iris, 8MP, FA Lens
Performance	
Focal Length	16 mm
F-Number	F2.8 ~ F16
Image Size	Φ11 mm(2/3")
Distortion	0.33%
Minimum Object Distance	0.1 m
Field of View	D (11.1 mm) : 37.39° H (8.45 mm) : 28.9° V (7.07 mm) : 24.33°
Mechanical	
Iris Control	Manual
Focus Control	Manual
Filter Thread	M27 × 0.5
Mount	C-Mount
Flange Back Length	17.526 mm
Dimension	Φ28.5 × 39.33 mm
Weight	57.1 g
Temperature	-10 ~ 50°C
General	
Certification	RoHS2.0

Dimension



Field of View

Extension (mm)	Working Distance (mm)		Magnification	Field of View(mm)					
				2/3"		1/1.8"		1/2"	
				H (8.45mm)	V (7.07mm)	H (7.38mm)	V (4.92mm)	H (6.22mm)	V (4.67mm)
5	near	20.98	-0.450	18.80	15.73	16.42	10.95	13.84	10.39
	far	33.66	-0.313	27.03	22.61	23.60	15.74	19.89	14.94
2	near	46.45	-0.262	32.25	26.98	28.17	18.78	23.74	17.82
	far	110.33	-0.125	67.51	56.49	58.96	39.31	49.70	37.31
1	near	65.58	-0.200	42.36	35.44	36.99	24.66	31.18	23.41
	far	237.84	-0.063	134.85	112.83	117.78	78.52	99.27	74.53
0		100	-0.134	63.47	53.05	55.39	36.86	46.64	34.98
		150	-0.095	89.78	75.05	78.36	52.16	65.99	49.50
		200	-0.073	115.89	96.90	101.17	67.36	85.22	63.93
		250	-0.060	141.90	118.68	123.89	82.51	104.37	78.31
		300	-0.050	167.87	140.41	146.58	97.64	123.49	92.67
		350	-0.044	193.81	162.12	169.24	112.74	142.59	107.01
		400	-0.039	219.72	183.81	191.88	127.84	161.68	121.34
		450	-0.034	245.63	205.49	214.51	142.93	180.76	135.66
		500	-0.031	271.52	227.17	237.14	158.01	199.83	149.97
		550	-0.028	297.41	248.83	259.75	173.09	218.89	164.28
		600	-0.026	323.29	270.50	282.36	188.17	237.95	178.59
		650	-0.024	349.16	292.15	304.97	203.24	257.01	192.90
		700	-0.023	375.03	313.81	327.57	218.31	276.06	207.21
		750	-0.021	400.88	335.46	350.17	233.40	295.12	221.53
		800	-0.020	426.76	357.11	372.77	248.45	314.16	235.82
		850	-0.019	452.63	378.76	395.37	263.52	333.21	250.11
	900	-0.018	478.49	400.41	417.97	278.58	352.26	264.41	
	950	-0.017	504.35	422.06	440.56	293.65	371.30	278.71	
	1000	-0.016	530.21	443.70	463.15	308.71	390.35	293.01	

HIKROBOT

Hangzhou Hikrobot Co. Ltd.
en.hikrobotics.com

© Hangzhou Hikrobot Co., Ltd. All Rights Reserved.

Hangzhou Hikrobot does not tolerate any infringement. Any organization or individual may not imitate or reproduce in whole or in part of the content. The data herein is based on Hikrobot's internal evaluation. Actual data may vary depending on specific configuration and operating condition. The information herein is subject to change without notice. All the content has been checked conscientiously. Nevertheless, Hikrobot shall not be liable to damages resulting from errors, inconsistencies or omissions.